







Commercial Construction

The Vista's quadpro treated structural steel frame is assembled with marine grade 316 stainless steel componentry and powder coated in a colour of your choice, for a smart, easy care, finish.

The sophisticated PVC formulation includes UV inhibitors that protect the fabric and the colour pigments from damage and fading, ensuring the longevity of the canopy.

An additional PVDF coating ensures ease of cleaning making it ideal for commercial environments.

Engineered for Performance

With umbrella weights between 260 – 360kg the Vista has been designed and engineered for permanent fixed installation outdoors.

Capable of withstanding wind speeds up to 118kph whilst open, you'll have ample time to retract the umbrella in changing weather conditions. Once closed, the Vista will stand safe and secure in winds up to 148kph, ready for future use.



Canopy Type



Dimensions



General Specifications

- · Shape Options: Hexagonal, Square, Rectangle.
- Canopy Type: Retractable, architectural grade high tensile, PVC canopy.
- Installation Method: Bolted base plate to existing concrete slab or footing. Installation via a Skyspan certified installer or competent tradesperson.
- Frame Construction: Quadpro treated structural steel column with marine grade 316 stainless steel catenary cables and componentry.
- Frame Finish: Powder coated in your preferred colour from the Skyspan™ colour range.
- Engineer Wind Rated: up to 118kph (W33) when open and up to 148kph (W41) when closed.

Umbrella Height

Packaged Weight

	L x W Approx	А	В	Kg Approx
Square 2.4	2380 x 2380mm	3350mm	2250mm	300
Square 3.0	3130 x 3130mm	3550mm	2250mm	314
Square 3.5	3470 x 3470mm	3555mm	2250mm	330
Square 4.0	4000 x 4000mm	3730mm	2410mm	347
Square 5.0	5000 x 5000mm	4153mm	2500mm	372
Hexagonal 4.4	3830 x 4415mm	3545mm	2150mm	270
Hexagonal 5.0	4960 x 4310mm	3635mm	2150mm	275
Hexagonal 5.6	4880 x 5610mm	3643mm	2270mm	280
Rectangular 4 x 3	3950 x 2950mm	3615mm	2370mm	330



